




Expansion joint profiles in hard-soft PVC for use with the thick-bed process



Application:

DURAFLEX thick-bed expansion joint profiles from Dural have been developed in order to prevent tension due to pressure on a flooring surface. They are used as dividers for stone-based surfaces (clinker pavings, ceramic tiles, natural stone pavings). With the soft section in the model, they absorb tensions due to pressure and damp them with no difficulty. This also prevents breakages to the pavings themselves.

The hard PVC exterior ensures that DURAFLEX thick-bed profiles also provide efficient protection for edges. Better protection for edges can only be achieved by using other materials (e.g. brass, stainless steel - see DURAFLEX TL range). The flexible form means that the profiles can also be installed subsequently to the rest of the paving. They can easily be used for subsequently generated expansion joints. DURAFLEX thick-bed profiles are available in heights of up to 65 mm. Their suitability for the function is also attested by a special certificate (Säurefließner Vereinigung e.V., D-30938 Großburgwedel).

Material:

DURAFLEX thick-bed profiles are made of environmentally-friendly hard-soft PVC. They are available in the following colours: white, beige, black, terracotta, grey, grey/transparent.

Properties:

DURAFLEX thick-bed profiles are mainly designed for use in industry. They are made using coloured PVC and are largely UV-resistant. Their usage with regard to chemical and mechanical resistance should nevertheless be assessed in each individual case.

Installation:

1. DURAFLEX thick-bed profiles appropriate to the height of the tiles should be selected.
2. Profiles should be placed flush with the surface and laid thus. Contact mortar should be used to ensure that the profiles are thoroughly embedded at the sides.
3. The adjoining surface should be moved flush against the profile and fully embedded in the mortar.
4. Any space between the profile and the tiles should be filled completely with grout.

Maintenance:

DURAFLEX thick-bed profiles do not require any special maintenance. Dirt may be removed using conventional cleaning agents. Cleaning agents should be free of hydrochloric and hydrofluoric acid and should not contain abrasives.

Data sheet

Material	Colors	Height
PVC	white / beige / black / terracotta / grey / grey-transparent	30 – 65 mm