


Thin-bed expansion joints profile with small legs



Application:

DURAFLEX expansion joint profiles by Dural are suitable for areas subject to medium amounts of wear and stresses. This includes offices and sales outlets. They can also be used outdoors (on balconies or facades). Their visible surface has a width of 8 mm, which corresponds to the customary width for expansion joints. When loads act at a point, legs 24 mm wide spread the load evenly throughout the flooring and the foundations.

The profiles are available in heights from 6 to 15 mm. They should be led using the thin-bed technique.

Important: any expansion joints in the foundations need to be followed precisely.

Material:

DURAFLEX expansion joint profiles are made of hard-soft PVC. That includes the legs. The following colour is available: grey.

Properties:

DURAFLEX expansion joint profiles are resistant to UV exposure and do not include emollients. They are resistant to all kinds of chemical stresses that are usually experienced by tiles. Damage to the visible surface due to deformation or scratching is unlikely under normal circumstances.

However, their usage with regard to chemical and mechanical resistance should be assessed in each individual case.

Installation:

1. DURAFLEX expansion joint profiles should be chosen to match the thickness of the tiles.
2. Tile adhesive should be applied around the junction using a serrated trowel.
3. Press the DURAFLEX profile into the adhesive bed and align it. Follow any existing joints in the foundations.
4. Spread mortar over the entire surface of the joint.
5. Press in tiles firmly and align them so that they are flush with the top edge of the profile. Lay the tiles without leaving any gaps.
6. Allow a joint of 2 mm around the profile itself.
7. Then fill the space between the tiles and the profile with grout.

Maintenance:

DURAFLEX expansion joint profiles do not require any special maintenance. They are resistant to bacteria and fungus and are "automatically" cleaned when the tiles are cleaned. Cleaning agents should be free of hydrochloric and hydrofluoric acid and should not contain abrasives.

Data sheet

Material	Colour	Height
PVC	grey	6 – 15 mm